

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)


PCT

(10) International Publication Number
WO 2004/033984 A1

- (51) International Patent Classification: F41C 23/10 (74) Agent: CRUTCHER, William, C.; McCormick Paulding & Huber, LLP, CityPlace II, 185 Asylum Street, Hartford, CT 06103 (US).
- (21) International Application Number: PCT/US2003/030684
- (22) International Filing Date: 25 September 2003 (25.09.2003) (81) Designated States (national): AE, AU, BA, BZ, CA, CN, CO, CR, DZ, EC, GE, HR, IL, IN, JP, KE, KR, LT, LV, MA, MG, MK, MX, NO, NZ, OM, PH, PL, SD, SG, SY, TN, UA, US, UZ, VN, YU, ZA.
- (25) Filing Language: English (84) Designated States (regional): Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (26) Publication Language: English
- (30) Priority Data: 60/417,023 7 October 2002 (07.10.2002) US Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (71) Applicant and
(72) Inventor: MOORE, Wildey, J. [US/US]; 45 Angevine Road, Warren, CT 06794 (US).

[Continued on next page]

(54) Title: FRAME CONSTRUCTION FOR WITH REMOVABLE SIDE PLATE



(57) Abstract: Frame construction for a firearm (10) with a frame (18) and a slide (12) constrained to move longitudinally between a forward and a rearward position but which is also removable from the frame. A recess (39) in the side of the frame contains the Kammer trigger mechanism (26, 38) that is accessible through a side opening (40) in the frame. A thin side plate (42) drops over the side opening and is held at its side edges and bottom edge by flanges (50) on the side plate overlapping congruent grooves in the frame and is held in place on top by the slide. After removing the slide in the conventional manner, the side plate can be slide upwardly and removed using a finger cutout (48) in the side plate.

WO 2004/033984 A1

WO 2004/033984 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

FRAME CONSTRUCTION WITH REMOVABLE SIDE PLATE

Cross Reference to Related Applications

5 This application claims the benefits of prior filed, co-pending U.S. provisional patent application Serial No. 60/417,023 filed on October 7, 2002.

Technical Field

 This invention relates to an improved frame construction for a firearm.
10 More particularly, it relates to an improved frame construction for a firearm of the type having a longitudinally movable slide on the frame and a hammer trigger mechanism in the frame for operating the firearm.

Background Art

15 A firearm, and in particular an autoloading or automatic firearm, is equipped with an external hammer that can be cocked to the rear and engaged with a sear and then tripped by squeezing the trigger which engages the sear by means of linkage releasing its engagement to the hammer (single action letoff). Alternatively, the hammer can be drawn to the rear for release and firing by
20 squeezing the trigger without first cocking the hammer. This is accomplished through the linkage system engaging the hammer with the trigger for the aforementioned purpose; pulling the hammer rearward and releasing it before it can be engaged by the sear (double action letoff).

 This invention relates to firearms functioning in the aforementioned
25 manner incorporating a hammer spring, usually located in an area behind the magazine well in the frame and consisting of various components to accomplish the single action and double action letoffs. Historically, it is not recommended that anyone but an accomplished gunsmith work on these mechanisms as they are complicated and improper assembly or disassembly is

very likely to occur. Usually, tools are required to disassemble the firearm, so as to gain access to the hammer trigger mechanism or action of the firearm. The invention addresses these issues by accomplishing the same objectives but with basic components that anyone with an aptitude for mechanics can easily understand, and enables access easily to the hammer trigger mechanism without the need of tools.

Accordingly, one object of the present invention is to provide a simplified frame construction giving access to the hammer trigger mechanism for a firearm.

Another object of the invention is to provide a simplified construction for gaining access to the firearm action without the need of tools.

Another object of the invention is to provide an improved frame construction which simplifies cleaning or repair of the hammer trigger mechanism.

Disclosure of Invention

An improved frame construction for a firearm of the type having a frame having a top planar surface, a slide constrained to move longitudinally between a forward and a rearward position with respect to the barrel, the slide defining a bottom planar surface extending parallel to the frame top surface, the slide being removable from the frame, a barrel disposed in the slide for receiving a cartridge, a firing pin longitudinally slidable in the slide so as to strike the cartridge, a hammer arranged to strike the firing pin, a trigger, and a hammer trigger mechanism arranged to release the hammer when the trigger is pulled, the improvement comprising the frame having a side opening beneath the slide commencing at the frame top surface and defining a recess in the side of the frame, the hammer trigger mechanism being disposed in the recess and accessible through the side opening, a side plate arranged to cover the side opening, the side plate and the frame opening having congruent interlocking

means arranged to permit only upward movement of the side plate, and the side plate having a top planar surface disposed to be held against upward movement by the slide bottom planar surface when the slide moves longitudinally between forward and rearward positions, the slide being removable from the frame to release the side plate for upward movement when the slide is removed.

Brief Description of Drawings

The invention will be better understood by reference to the following description, taken in connection with the accompanying drawings, in which:

Fig. 1 is a side elevational drawing, partly in section, of portions of a semi-automatic firearm,

Fig. 2 is a bottom plan view of the slide of the firearm,

Fig. 3 is a top plan view of the frame of the firearm,

Fig. 4 is a top plan view of the major components of the hammer trigger mechanism,

Fig. 5 is a side elevational drawing of the firearm showing the side plate location,

Fig. 6 is a top plan view of the side plate used in the present invention,

Fig. 7 is a side elevational view of the side plate used in the present invention, and

Fig. 8 is a bottom plan view of the side plate used in the present invention.

Best Mode for Carrying Out the Invention

Referring now to **Fig. 1** of the drawing, the invention is described as embodied in a semi-automatic firearm **10** of the type using a spring-loaded cartridge magazine (not shown) and having a reciprocating slide **12** adapted to move from a forward position in a rearward direction against a recoil spring

(not shown) when a cartridge 14 is fired. During the rearward movement, the shell of cartridge 14 is ejected, and during the return forward movement, a new cartridge is stripped from the magazine by the extractor and inserted into the bore of a barrel 16 in a manner well known in the art. Slide 12 is reciprocable in tracks upon a frame 18. A hammer 20 is pivotably mounted on frame 18 to strike a firing pin 22, which is longitudinally slidable in the slide 12 so as to strike the rear of cartridge 14. A trigger 24 is pivotably mounted in the frame and connected to push or pull a transfer bar 26. Slide 12 includes a cam surface 28, which cooperates with a first finger 30 to raise or lower the end of transfer bar 26 when the transfer bar is pushed or pulled longitudinally by the trigger 24. The foregoing list of elements describes one construction for a hammer trigger mechanism or action known in the prior art. Other types of hammer trigger mechanisms or actions are also known, the details of which are not relevant, since any type of hammer trigger mechanism is applicable to the present invention. The invention relates to improvements in the frame construction to enable easy access to the hammer trigger mechanism, as illustrated in the following figures.

A bottom view of slide 12 is shown in Fig. 2, having planar bottom surfaces 36, 37. A top view of the frame 18, with slide 12 removed is shown in Fig. 3. Frame 18 includes planar top surfaces 32, 34. Planar surfaces 36, 37 of slide 12 extending longitudinal and parallel to the top planar surfaces 32, 34 of the frame 18.

Fig. 3 illustrates the hammer 20 and trigger 24 disposed in a recess 39 of the frame. The hammer trigger mechanism includes the transfer bar 26, a sear 38 and other pins and linkages not material to the present invention. Fig. 4 illustrates the hammer trigger mechanism without the frame, having the same elements as identified in Fig. 3.

In accordance with the present invention, the hammer trigger mechanism of Fig. 4 is disposed in the recess 39. Recess 39 is accessible

through a side opening 40 cut in the side of the frame 18. The elements of the hammer trigger mechanism may be accessed and removed for cleaning and/or repair through the side opening 40. Side opening 40 is closed and covered by a side plate 42 shown in Fig. 5 of the drawing.

5 Side plate 42 is illustrated in Figs. 6, 7 and 8 of the drawing as a thin metal plate having the same shape as the side opening 40. As shown in Fig. 6, a top edge 44 has a planar surface. The side and bottom edges 46, shown in Fig. 7 are milled out to leave a narrow flange 50 running around the side and bottom edges 46. The flange is interrupted by a cutout 48. Fig. 8, showing the
10 bottom plan view indicates the small flange 50.

 Referring to Fig. 3 of the drawing, the side plate 42 is shown covering the side opening 40 leading into recess 39. The bottom and side of the side opening 40 is cut out with a groove congruent to the bottom and side edges of side plate 42 to receive flange 50. Thus congruent interlocking edges, with the
15 exception of the top side of side opening 40 permit only upward movement of the side plate 42 and the frame. When side plate 42 is in the frame, its top planar edge 44 is flush with the top planar surfaces 32, 34 of the frame and thus held in position by slide 12.

 Slide 12 is removable from frame 18 in a manner well known to those
20 skilled in the art by removing a slide retainer pin. When the slide is removed, side plate 42 may be moved upwardly with the assistance of the cutout 48 in the side plate, without the aid of tools. In this matter, access to the hammer trigger mechanism from the side of the frame through a side plate removable without tools provides a substantial advantage over prior art firearms of this
25 type.

 While there has been described what is considered to be the preferred embodiment of the invention, other modifications will occur to those skilled in the art. It is desired to secure all such modifications as fall within the true spirit and scope of the invention.

Claims

1. An improved frame construction for a firearm of the type having a frame having a side terminating at a top planar surface, a slide constrained to move longitudinally between a forward and a rearward position, said slide defining a bottom planar surface extending parallel to and slidable across said frame top surface, said slide being removable from the frame, a barrel for receiving a cartridge, a firing pin longitudinally movable in the slide so as to strike the cartridge, a hammer arranged to strike the firing pin, a trigger, and a hammer trigger mechanism arranged to release the hammer when the trigger is pulled, **said improvement being characterized by:**

said frame having a side opening commencing at the frame top surface and defining a recess in the side of the frame facing said side opening,

said hammer trigger mechanism being disposed in said recess and accessible through said side opening,

a side plate arranged to cover said side opening, said side plate having a top planar surface disposed to be held in place by said slide bottom planar surface when the slide moves longitudinally between forward and rearward positions, said slide being removable from the frame to release the side plate when the slide is removed.

2. Improved frame construction in accordance with Claim 1, wherein said side plate and said frame opening have congruent interlocking edges arranged to permit only upward movement of the side plate, and wherein said slide bottom planar surface prevents upward movement of the side plate when the slide moves longitudinally between forward and rearward positions.

3. Improved frame construction in accordance with Claim 2, wherein said side plate includes side edges and a bottom edge each defining a flange, and

wherein said side opening includes side edges and a bottom edge each defining a groove, said flange and said groove arranged and dimensioned to retain the side plate against outward movement with respect to the frame.

5 4. Improved frame construction in accordance with Claim 2, wherein said side plate bottom edge is interrupted to provide a cutout adapted for use to move the side plate in an upward direction to remove the side plate after the slide has previously been removed.

10 5. Improved frame construction in accordance with Claim 1, wherein the length of said side plate between its side edges is substantially the same as the distance between said trigger and said hammer of the firearm.




Fig. 1

2/3




Fig. 2




Fig. 3




Fig. 4




Fig. 5

3/3




Fig. 6




Fig. 7




Fig. 8

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/30684

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : F41C 23/10
US CL : 42/69.03, 71.02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
U.S. : 42/69.03, 71.02; 89/163

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5, 669, 169 A (SCHMITTER et al) 23 September 1997 (23.09.1997), see entire disclosure	1-5
A	US 6, 000, 162 A (HOCHSTRATE) 14 December 1999 (14.12.1999), see entire disclosure	1-5
A	US 4, 967, 503 A (FARAAR) 06 November 1990 (06.11.1990), see entire disclosure	1-5

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

Special categories of cited documents:	
* "A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

31 January 2004 (31.01.2004)

Date of mailing of the international search report

02 MAR 2004

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

Facsimile No. (703)305-3230

Authorized officer

Stephen M. Johnson

Telephone No. (703) 306-4158